
DEEP SEA DRILLING PROJECT(U) LAMONT-DOHERTY GEOLOGICAL OBSERVATORY PALISADES NY R N ANDERSON JAN 85 LDGO-CU-5-21507 N00014-83-K-2020 F/G 8/7 UNCLASSIFIED NL

1/1

AD-A150 624



MICROCOPY RESOLUTION TEST CHART NATIONAL BUREAU OF STANDARDS-1963-A



LAMONT-DOHERTY GEOLOGICAL OBSERVATORY
OF COLUMBIA UNIVERSITY
Palisades, New York 10964

FINAL TECHNICAL REPORT

for

ONR Research Contract NO0014-83-K-2020

Deep Sea Drilling Project

by

R. N. Anderson

January 1985



This document has been approved for public release and sale; its distribution in val. hed.

R.N. Anderson

Multi-channel, full waveform sonic logs were recorded as part of a complete suite of geophysical logs in Deep Sea Drilling Project borehole 556 into 37-million-year-old crust on the western flank of the Mid-Atlantic Ridge. The lithostratigraphy is unusual in that two highly altered serpentinite fracture zones were encountered which crosscut relatively fresh gabbros. The fracture zones are each approximately 50 feet thick, are serpentinized at their margins, and grade into much less extensively altered gabbros at their centers.


Spectral analyses of windowed compressional and shear wave coda recorded by the multi-channel sonic log across this interval show that the fracture zones are not only strong energy attenuators, but are also acting as differential high-pass filters of the sonic energy. These fault zones can be easily identified from an apparent Q log derived from the change in energy across the receivers whereas neither Vp/Vs nor Poisson's Ratio show strong inflections at these depths. A probable reason for the latter is an increase in density associated with serpentinization, so that the fracture zones are actually of higher density than the surrounding rock.

In addition, the shear wave energy displays a filtering effect across the highly altered fracture zones. That is, both integrated energy content and center frequency drop across the fault zone.

Chemical analyses of cores, as well as nuclear and electrical logs allow us to characterize the change in porosity, alteration state and pore shape from the gabbro, which is highly fractured, to the serpentinite, in which most pore spaces are filled with plate-like and fibrous mixed-layer clays, talc and serpentine mineralization.

An acoustic attenuation model was developed in which the filter characteristics of the fracture zone are associated with venting, the differential loss of low-frequency energy, dependent on the dimensions of the available pore spaces, and fractures as they are filled with alteration minerals. In retrospect, the best way to have unambiguously identified the fracture zones at DSDP hole 556 was from shear wave filter characteristics (frequency-energy changes), rather than from 0, Vp/Vs, or Poisson's Ratio changes. This technique has important applications in the identification of fractured reservoirs.

The other Mid-Atlantic Ridge wells, DSDP 564 and 558 were logged over too short an interval to perform the above analyses.



REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
i l	ESSION NO. 3. RECIPIENT'S CATALOG NUMBER
N00014-83K-2020	
4. TITLE (and Substite)	S. TYPE OF REPORT & PERIOD COVERED
	Final
Peep Sea Drilling Project	6. PERFORMING ORG. REPORT NUMBER 5-21507
7. AUTHOR(a)	8. CONTRACT OR GRANT NUMBER(*)
Roger N. Anderson	N00004-83K-2020
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
Lamont-Doherty Geological Observatory of Col University, Low Library, New York,N.Y. 10027	
11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE
Department of the Navy, O.N.R.	January 1985
Code 425 AC Arlington, VA 22217	13. NUMBER OF PAGES
14. MONITORING AGENCY NAME & ADDRESS(II different from Controll	ing Office) 15. SECURITY CLASS. (of this report)
	unclassified
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)	
Approved for public release, distribution	n unlimited
17. DISTRIBUTION STATEMENT (of the abetract entered in Block 20, if different from Report) ——	
18. SUPPLEMENTARY NOTES	
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)	
multi-channel full waveform sonic logs, lithostrātigraphy, fracture, fault zones	
spectral analyses, compressional and shear coda	
20. ABSTRACT (Continue on reverse elde if necessary and identify by block number)	
Several previously recorded Deep Sea Drilling Project wells were re-examined to determine compressional and shear velocities in oceanic crust. Only 3 wells had sufficiently high quality sonic logs run in them to provide this information.	
Schlumberger then processed these 3 wells all in 17 million year old sea floor on the western flank of the Mid-Atlantic Pidge. Vp,Vs, Poisson's Ratio, amplitude	

and center frequency of the compressional and shear coda were calculated. The

results were published by Diachek et al. Acoustical Soc. Amer. 1984.

DD 1 JAN 73 1473 EDITION OF 1 NOV 65 18 OBSOLETE S/N 0107-014-6601

END

FILMED

3-85

DTIC